

LOAD LIMITER SETTING 권고치

© POWER SOURCE : AC 3PH 220V, 380V, 440V, 460V, 480V 60Hz

HOIST		MOTOR 용 량 (Kw x P)	220V			380V			440V			460V			480V		
용 량 (TON)	S.T.D		정격전류 (A) 100%부하시	LOAD LIMITER(110%)		정격전류 (A) 100%부하시	LOAD LIMITER (110%)		정격전류 (A) 100% 부하시	LOAD LIMITER (110%)		정격전류 (A) 100% 부하시	LOAD LIMITER (110%)		정격전류 (A) 100% 부하시	LOAD LIMITER (110%)	
				TIME(SEC)	SETTING(A)		TIME (SEC)	SETTING (A)		TIME (SEC)	SETTING (A)		TIME (SEC)	SETTING (A)		TIME (SEC)	SETTING (A)
0.25, 0.5	S.T.D	0.5 x 4	2.9	1.5	3.19	1.7	1.5	1.87	1.5	1.5	1.65	1.45	1.5	1.595	1.4	1.5	1.54
1, 2	S.T.D	1.5 x 4	6.4	1.5	7.04	3.7	1.5	4.07	3.2	1.5	3.52	3.1	1.5	3.41	2.9	1.5	3.19
	DUAL	1.5/0.75 x 4/8	6.3/4.9	1.5	6.93/5.39	3.6/2.8	1.5	3.96/3.08	3.1/2.4	1.5	3.41/2.64	3/2.3	1.5	3.3/2.53	2.9/2.2	1.5	3.19/2.42
2.8(3),5	S.T.D	3.5 x 4	15	1.5	16.5	8.7	1.5	9.57	7.5	1.5	8.25	7.2	1.5	7.92	6.9	1.5	7.59
	DUAL	3.5/1.75 x 4/8	15.2/12.1	1.5	16.7/13.3	8.8/7.1	1.5	9.68/7.81	7.6/6.1	1.5	8.36/6.71	7.3/5.8	1.5	8.03/6.38	7/5.6	1.5	7.7/6.16
1.5 .3	S.T.D	2.5 x 4	9.5	1.5	10.45	5.5	1.5	6.05	4.8	1.5	5.28	4.5	1.5	4.95	4.4	1.5	4.84
	DUAL	2.5/1.25 x 4/8	9.5/4.8	1.5	10.5/5.28	5.5/2.8	1.5	6.05/3.08	4.8/2.4	1.5	5.28/2.64	4.6/2.3	1.5	5.06/2.53	4.4/2.2	1.5	4.84/2.42