



SPECIFICATION		
HOISTING LOAD	0.5 TON	
TESTING LOAD	0.625 TON	
LIFTING HEIGHT	Min. 3.5~20 M	
HOISTING	SPEED	4.2 M/MIN
	MOTOR	0.5 Kw x 4 POLE
TRAVERSING	SPEED	20 M/MIN
	MOTOR	0.2 Kw x 4 POLE
POWER SUPPLY	3Φ-220,380,440V-60Hz	
CONTROLL VOLTAGE	1Φ-110V-60Hz	
OPERATING METHOD	PUSH BUTTON TYPE	
LOAD CHAIN SPEC.	Φ5.0 x 15P x 2 FALLS	
RATING	30 MIN	
NET WEIGHT	Min. 53 KG	

1300	T/S ELEC. ASS'Y			1	
1200	TROLLEY MOTOR ASS'Y			1	
1100	TROLLEY PART ASS'Y			1	
710	OVER LIMITER			1	
700	ELEC. ASS'Y			1	
600	HOIST MOTOR ASS'Y			1	
500	BUCKET ASS'Y			1	
400	BOTTOM HOOK ASS'Y			1	
200	GEAR BOX ASS'Y			1	
100	CENTER FRAME ASS'Y			1	

NO.	DESCRIPTION	MAT'L	SIZE	Q'TY	REMARK
DESIGNED	APPROVED	DATE	SCALE	DWG. NO.	
김광진		2000.12.22.	1 / 3		H02-000-ST



TITLE OF PROJECT 0.5TON MONO RAIL TYPE
ELEC. CHAIN HOIST GENERAL ASSEMBLY